

Conventional Manual Call Point- MCP1A-525IMC

Indoor Call Point Range



Product Benefits

- **Unique 'Plug & Play' installation concept**
- **Total 'Flex-Ability' in the choice of operating element**
- **Anti-Tamper facility**
- **Enhanced aesthetics**
- **Fully approved to the latest standards**
- **Backward compatibility**

LPCB Approved



Product Overview

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP1A-525IMC indoor call point range.

Installation time and ultimately cost, are of paramount importance to any fire or security installer. The MCP1A-525IMC range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. The new MCP1A-525IMC product utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

The new MCP1A-525IMC comes with resettable element as standard.

The MCP1A-525IMC indoor call point products also help preserve the integrity of the overall system as illegal removal of the product lid will result in the call point operating and the system going into alarm.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard. The MCP1A-525IMC product version is supplied with both a resistor and normally open clean contact electrical options. These options are easily utilised by simply connecting the terminal block to the required connection in the back of the MCP1A-525IMC product.

Electrical, Environmental & Mechanical Specification

Connection Details:	See Instruction manual
Cable Termination:	0.5-2.5mm ²
Maximum Voltage:	30VDC
Current Rating (switch only):	2 Amps
Humidity:	93± 3% non-condensing
Operating Temperature:	-10°C to +55°C
Storage Temperature:	-10°C to +55°C
Ingress Protection (IP) Rating:	IP24D
Material:	PC/ABS
Weight:	180g
Colour:	Red, Ral 3001

Order Code

No Break Resettable Conventional Manual Call Point- Branded Context Plus- (LPCB Approved).	MCP1A-525IMC
---	--------------